

ReceiptNOW®

Stackable Teller Receipt Printer



The ReceiptNOW fits beneath your check scanner to deliver fast, convenient thermal receipts. Its stacked design saves counter space and reduces cable clutter at the teller station. With minimal moving parts and no ink or ribbons to replace, the thermal printer offers faster printing and less maintenance than most inkjet models.

DESIGNED FOR:

- SmartSource® Professional



KEY FEATURES & BENEFITS

- Standard USB 2.0 Connectivity
- Modular Design Saves Counter Space
- Easy Slide-Out Drawer for Paper Replacement
- No ink required
- Fast and Quiet Thermal Printing
- Print Graphics on Your Receipts
- Engineered for Durability

STACKABLE DESIGN

ReceiptNOW is engineered to fit beneath your check scanner so you can enjoy a cleaner more efficient workspace. ReceiptNOW is designed to fit beneath a range of SmartSource and TellerScan products.

CUSTOMIZE RECEIPTS

ReceiptNOW enables users to customize the look and feel of their receipts. Options include top and bottom logos, border messages, watermarks, and windows true type fonts.



Compatibility

- USB interface
- Full 108 standard and international fonts with barcode
- Prints on standard, security, non-BPA and 2-color paper
- International power compliant
- Uses international standardized codes

USB Connectivity

The ReceiptNOW printer offers a traditional USB-connected configuration for easy setup and use in any environment.

Features

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Fits the largest paper rolls
- Full or partial paper cut



Printer Dimensions

Height: 5.4 in (13.72 cm)

Width: 6.1 in (15.5 cm)

Length: 15.3 in (38.86 cm)

Weight: 7.2 lbs (3.2 kg)

Printing / Feed / Cut

Direct Thermal Printer

Maximum print speed is 250mm/sec,

two-color printing speed 100mm/sec,

gray print speed 100mm/sec.

Resolution: 203 x 180 dpi

95 Alphanumeric, 13 International Characters with Kanji

True Type Fonts available when being driven as a

Windows printer

1D/2D Bar Code Fonts

512K On-board Logo Flash

Full/Partial Auto Cutter

Controls

On/Off Switch

Paper Empty/Low LED's with audible alerts

Paper Feed Button

Paper Width Adjustment

Power Indicator

Paper / Loading

Standard, Security, Non-BPA, 2-color Paper

Paper Widths: 2.4 in to 3.25 in (6.1 cm to 8.3 cm)

Paper Roll Diameter: 3.25 in (8.3 cm)

Slide Out Tray, Drop-in Paper

Connectivity

USB 2.0

Standard ESC/POS Command Set

OPOS & JavaPOS, Auto Status Back (ASB)

Included Accessories

USB 2.0 cable

International 100-240VAC, 50/60Hz power supply

Graphic Receipt Customization

Multiple Graphics Can be Placed Anywhere

Custom Messages

Watermarks

Supported Operating Systems

Windows 11/10, (x86 and x86-64)

Standard Warranty

Three years pursuant to Digital Check Corp.'s limited product

warranty

Environmental

Operating Temperature: 41° - 104° F (5° - 40° C)

Operating Humidity: 20 - 90% non-condensing

Certifications

Operating Temperature: 60° - 90° F (15° - 32° C)

Operating Humidity: 35 - 85% non-condensing

Certifications

Safety:

UL, cUL, CE

Emissions:

FCC: Class B

ICES-003

CE

VCCI

Power Supply Efficiency:

DOE Level VI

RoHS Compliant

Part Number

SRN2PTR-USB (ReceiptNOW Original with USB)